














## DALI Master Panel

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
TD1-S	1 Zone DIM DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT6) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1 Zone, 1 DALI address, support DT6 dimming.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 4 Scene Memory.</li> <li>● Match with RF 2.4G single zone or multiple zone remote control optional.</li> </ul>	DALI Constant Voltage LED Controller: DA1, DA1-S DALI Constant Current LED Controller: DA4-C DALI Constant Voltage LED Driver: LPV-150DA-24 DALI Constant Current LED Driver: DA-12A, DA-20A, CXD-21A DALI Triac Dimmer: DT, DT-B DALI 0-10V Dimmer: DV, DV1 DALI Bus Power: DA-PS-L RF Remote Control: R11, RT1	/
TD1-4S	4 Zone DIM DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT6) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 4 Zone, 4 DALI address (sequential allocation), support DT6 dimming.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 3 Scene Memory.</li> <li>● Optional 4-zone dimming RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA1, DA1-S DALI Constant Current LED Controller: DA4-C DALI Constant Voltage LED Driver: LPV-150DA-24 DALI Constant Current LED Driver: DA-12A, DA-20A, CXD-21A DALI Triac Dimmer: DT, DT-B DALI 0-10V Dimmer: DV, DV1 DALI Bus Power: DA-PS-L 4 Zone RF Remote Control: RT6, RS1	/
TL4-1D	1/4 Zone DIM DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT6) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1/4 Zone, 1/4 DALI address (sequential allocation), support DT6 dimming.</li> <li>● Rotary encoder switch selects 1 zone or 4 zone mode, DALI address, supports grouping, unicast and broadcast.</li> <li>● 4-scene memory in 1 Zone mode.</li> <li>● Optional 1/4-zone dimming RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA1, DA1-S DALI Constant Current LED Controller: DA4-C DALI Constant Voltage LED Driver: LPV-150DA-24 DALI Constant Current LED Driver: DA-12A, DA-20A DALI Triac Dimmer: DT, DT-B DALI 0-10V Dimmer: DV, DV1 DALI Bus Power: DA-PS-L RF Remote Control: R11, RT1, RT6, RS1	/
TD2-S	1 Zone CCT DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1 Zone, 1 DALI address, support DT8-TC color temperature.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 4 Scene Memory.</li> <li>● Match with RF 2.4G single zone or multiple zone color temperature RF remote control optional.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Constant Current LED Controller: DA4-C DALI CCT Constant Current LED Driver: DA-12A-2, DA-20A-2, CXD-21A-2 DALI Bus Power: DA-PS-L Color Temperature RF Remote Control: R12, RT2	/
TD2-4S	4 Zone CCT DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 4 Zone, 4 DALI address, (sequential allocation), support DT8-TC color temperature.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 3 Scene Memory.</li> <li>● Optional 4-zone color temperature RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Constant Current LED Controller: DA4-C DALI CCT Constant Current LED Driver: DA-12A-2, DA-20A-2, CXD-21A-2 DALI Bus Power: DA-PS-L 4 Zone Color Temperature RF Remote Control: RT7, RS2	/
TL4-2D	1/4 4 Zone CCT DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1/4 Zone, 1/4 DALI address (sequential allocation), support DT8-TC color temperature.</li> <li>● Rotary encoder switch selects 1 zone or 4 zone mode, DALI address, supports grouping, unicast and broadcast.</li> <li>● 4-scene memory in 1 Zone mode.</li> <li>● Optional 1/4-zone color temperature RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Constant Current LED Controller: DA4-C DALI CCT Constant Current LED Driver: DA-12A-2, DA-20A-2, CXD-21A-2 DALI Bus Power: DA-PS-L Color Temperature RF Remote Control: R12, RT2, RT7, RS2	/
TD3-S	Single Zone RGB DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1 Zone, 1 DALI address, support DT8-RGB.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 4 Scene Memory.</li> <li>● Supports multiple jump or fade dynamic effects.</li> <li>● Match with RF 2.4G single zone or multiple zone RGB RF remote control optional.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Constant Current LED Controller: DA4-C DALI Bus Power: DA-PS-L RGB RF Remote Control: R13, RT4	/
TD3-4S	4 Zone RGB DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 4 Zone, 4 DALI address, (sequential allocation), support DT8-RGB.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 3 Scene Memory.</li> <li>● Optional 4-zone RGB RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Constant Current LED Controller: DA4-C DALI Bus Power: DA-PS-L 4 Zone RGB RF Remote Control: RT9, RS4	/
TD4-S	1 Zone RGBW DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1 Zone, 1 DALI address, support DT8-RGBW.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 4 Scene Memory.</li> <li>● Supports multiple jump or fade dynamic effects.</li> <li>● Match with RF 2.4G single zone or multiple zone RGBW RF remote control optional.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Constant Current LED Controller: DA4-C DALI Bus Power: DA-PS-L RGB RF Remote Control: RT4	/



TD4-4S	4 Zone RGBW DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 4 Zone, 4 DALI address, (sequential allocation), support DT8-RGBW.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 3 Scene Memory.</li> <li>● Optional 4-zone RGBW RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA4-M, DA4-L, DA4-D DALI Bus Power: DA-PS-L 4 Zone RGB RF Remote Control: RT9, RS4	/
TD5-S	1 Zone RGB+CCT DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 1 Zone, 1 DALI address, support DT8-TC, DT8-RGB.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 4 Scene Memory.</li> <li>● Supports multiple jump or fade dynamic effects.</li> <li>● Match with RF 2.4G single zone or multiple zone RGB+CCT RF remote control optional.</li> </ul>	DALI Constant Voltage LED Controller: DA5-L DALI Bus Power: DA-PS-L RGB+CCT RF Remote Control: RT5	/
TD5-4S	4 Zone RGB+CCT DALI Master Touch Panel		Power supply: DALI bus/24VDC Input signal: Touch key, RF 2.4GHz Output signal: DALI (DT8) Control distance: 10m (Barrier-free space) Product size: 86x86x34.5mm (LxWxH)	<ul style="list-style-type: none"> <li>● 4 Zone, 4 DALI address, (sequential allocation), support DT8-TC, DT8-RGB.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● 3 Scene Memory.</li> <li>● Optional 4-zone RGB+CCT RF remote control.</li> </ul>	DALI Constant Voltage LED Controller: DA5-L DALI Bus Power: DA-PS-L 4 Zone RGB+CCT RF Remote Control: RT10	/
TD-K	RF DALI Master Rotary Panel		Power supply: DALI bus/24VDC Input signal: Rotary knob, RF 2.4GHz Output signal: DALI (DT6/DT8) Control distance: 20m (Barrier-free space) Product size: 86x86x43mm (LxWxH)	<ul style="list-style-type: none"> <li>● 5 in 1 function, support single color, color temperature, RGB, RGBW, RGB+CCT control.</li> <li>● Short press to switch, double press to switch the color, rotate knob to adjust the brightness, color temperature or RGB color.</li> <li>● Optional single-zone or multi-zone RF remote control for the same light type.</li> <li>● 1 DALI address, support DT6 dimming, DT8-TC color temperature, DT8-RGB, DT8-RGBW and DT8-RGB+CCT.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● For RGB, RGBW, RGB+CCT light types, supports multiple jump or fade dynamic effects.</li> </ul>	DALI Constant Voltage LED Controller: DA1, DA4, DA4-M, DA4-L, DA5-L DALI Constant Current LED Controller: DA4-C DALI Constant Voltage LED Driver: LPV-150DA-24 DALI Constant Current LED Driver: DA-12A, CXD-21A DALI CCT Constant Current LED Driver: DA-12A-2, CXD-21A-2 DALI Triac Dimmer: DT, DT-B DALI 0-10V Dimmer: DV, DV1 DALI Bus Power: DA-PS-L RF Remote Control: R11, R12, R13, RT1, RT2, RT4, RT5	/
TD-K(WT)	WiFi&RF DALI Master Rotary Panel		Power supply: DALI bus/24VDC Input signal: Rotary knob, WiFi, RF 2.4GHz Output signal: DALI (DT6/DT8) Control distance: 20m (Barrier-free space) Product size: 86x86x43mm (LxWxH)	<ul style="list-style-type: none"> <li>● 5 in 1 function, support single color, color temperature, RGB, RGBW, RGB+CCT control.</li> <li>● Short press to switch, double press to switch the color, rotate knob to adjust the brightness, color temperature or RGB color.</li> <li>● Tuya APP cloud control, support on/off, color temperature and brightness adjust, delay turn on/off light, timer run, scene edit and music play function.</li> <li>● Voice control, support for Amazon Alexa, Tmall Genie speakers.</li> <li>● Optional single-zone or multi-zone RF remote control for the same light type.</li> <li>● 1 DALI address, support DT6 dimming, DT8-TC color temperature, DT8-RGB, DT8-RGBW and DT8-RGB+CCT.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● For RGB, RGBW, RGB+CCT light types, supports multiple jump or fade dynamic effects.</li> </ul>	DALI Constant Voltage LED Controller: DA1, DA4, DA4-M, DA4-L, DA5-L DALI Constant Current LED Controller: DA4-C DALI Constant Voltage LED Driver: LPV-150DA-24 DALI Constant Current LED Driver: DA-12A, CXD-21A DALI CCT Constant Current LED Driver: DA-12A-2, CXD-21A-2 DALI Triac Dimmer: DT, DT-B DALI 0-10V Dimmer: DV, DV1 DALI Bus Power: DA-PS-L RF Remote Control: R11, R12, R13, RT1, RT2, RT4, RT5	/
TD-K(WZ)	Zigbee&RF DALI Master Rotary Panel		Power supply: DALI bus/24VDC Input signal: Rotary knob, Zigbee 3.0, HUE APP, RF 2.4GHz Output signal: DALI (DT6/DT8) Control distance: 20m (Barrier-free space) Product size: 86x86x43mm (LxWxH)	<ul style="list-style-type: none"> <li>● 5 in 1 function, support single color, color temperature, RGB, RGBW, RGB+CCT control.</li> <li>● Short press to switch, double press to switch the color, rotate knob to adjust the brightness, color temperature or RGB color.</li> <li>● Tuya APP cloud control, support on/off, color temperature and brightness adjust, delay turn on/off light, timer run, scene edit and music play function.</li> <li>● Philips HUE APP control by connect with Philips HUE bridge.</li> <li>● Voice control, support for Amazon Alexa, Tmall Genie speakers.</li> <li>● Optional single-zone or multi-zone RF remote control for the same light type.</li> <li>● 1 DALI address, support DT6 dimming, DT8-TC color temperature, DT8-RGB, DT8-RGBW and DT8-RGB+CCT.</li> <li>● Rotary encoder switch selects DALI address, supports grouping, unicast and broadcast.</li> <li>● For RGB, RGBW, RGB+CCT light types, supports multiple jump or fade dynamic effects.</li> </ul>	DALI Constant Voltage LED Controller: DA1, DA4, DA4-M, DA4-L, DA5-L DALI Constant Current LED Controller: DA4-C DALI Constant Voltage LED Driver: LPV-150DA-24 DALI Constant Current LED Driver: DA-12A, CXD-21A DALI CCT Constant Current LED Driver: DA-12A-2, CXD-21A-2 DALI Triac Dimmer: DT, DT-B DALI 0-10V Dimmer: DV, DV1 DALI Bus Power: DA-PS-L RF Remote Control: R11, R12, R13, RT1, RT2, RT4, RT5	/



TS4-D	4 Buttons DALI Master Touch Panel		Power supply:DALI bus/24VDC Input signal:Rotary knob Output signal:DALI (DT6) Proudct size:86x86x34.5mm(LxWxH)	<ul style="list-style-type: none"> <li>● 4 DALI address(sequential allocation).</li> <li>● 4 Touch buttons to realize scene recall,zoning switch and dimming function.</li> <li>● Rotary encoder switch selects DALI address,support scene, group, unicast and broadcast mode.</li> <li>● Proximity sensing, automatic blue backlight.</li> </ul>	DALI Constant Voltage LED Controller:DA1,DA1-S DALI Constant Current LED Controller:DA4-C DALI Constant Voltage LED Driver:LPV-150DA-24 DALI Constant Current LED Driver:DA-12A,DA-20A,CXD-21A DALI Triac Dimmer:DT,DT-B DALI 0-10V Dimmer:DV,DV1 DALI Switch:DH,DH1 DALI Bus Power:DA-PS-L	/
DA-4S	4 Push Button DALI Dimmer		Power supply:DALI bus Input signal:1-4push switch signal Output signal:DALI (DT6) Proudct size:52x52x27mm(LxWxH)	<ul style="list-style-type: none"> <li>● 4 DALI address(sequential allocation).</li> <li>● External 1-4 digit push button control to realize scene recall,zoning switch and dimming function.</li> <li>● Rotary encoder switch selects DALI address,support scene, group, unicast and broadcast mode.</li> <li>● Easy to be placed in standard wall junction box behind a push switch.</li> </ul>	DALI Constant Voltage LED Controller:DA1,DA1-S DALI Constant Current LED Controller:DA4-C DALI Constant Voltage LED Driver:LPV-150DA-24 DALI Constant Current LED Driver:DA-12A,DA-20A,CXD-21A DALI Triac Dimmer:DT,DT-B DALI 0-10V Dimmer:DV,DV1 DALI Switch:DH,DH1 DALI Bus Power:DA-PS-L	/

**DALI Bus Power**

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
DA-P	Push Switch DALI Dimmer +DALI Bus Power		Input voltage:100-240VAC Input signal:AC Push Switch Output signal:DALI Power output:DC16V, MAX.100mA Proudct size:52x52x27mm(LxWxH)	<ul style="list-style-type: none"> <li>● Used as a DALI bus power supply to power the DALI system.</li> <li>● External push switch,used as DALI dimming master.</li> <li>● Dimming speed adjustable by rotary knob.</li> <li>● Rotary encoder switch selects DALI address,support scene, group, unicast and broadcast mode.</li> <li>● Easy to be placed in standard wall junction box behind a push switch.</li> </ul>	DALI Constant Voltage LED Controller:DA1,DA1-S DALI Constant Current LED Controller:DA4-C DALI Constant Voltage LED Driver:LPV-150DA-24 DALI Constant Current LED Driver:DA-12A,DA-20A,CXD-21A DALI Triac Dimmer:DT,DT-B DALI 0-10V Dimmer:DV,DV1	<b>DA-P, DA-PS-L Contrast:</b> <b>Common:</b> 1. All can be used as a bus power supply to power the DALI system. <b>Difference:</b> 1. The bus output current is different: DA-PBus output current max.100mA, DA-PS-LBus output current max.200mA. 2. Working method is different: DA-P can also be used as a DALI dimming master control. DA-PS-L can also be used as a DALI signal repeater.
DA-PS-L	DALI Bus Power Supply & Repeater		Input voltage:100-240VAC Input/Output signal:DALI Power output:DC16V, MAX.200mA Proudct size:131x37x20.5mm(LxWxH)	<ul style="list-style-type: none"> <li>● Used as a DALI bus power supply to power the DALI system.</li> <li>● Enhancement and transmission of DALI signals(bidirectional).</li> <li>● For extending the DALI line length,Max.300m.</li> <li>● Supports star or cascade connections.</li> </ul>	DALI Master Touch Panel:TD1-S,TD1-4S,TS4-D Push Button DALI Dimmer:DA-4S	

**DALI Converter**

Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
DA-M	RF-DALI Converter		Power supply:DALI bus/24VDC Input signal:RF 2.4GHz Output signal:DALI Control distance:30m(Barrier-free space) Proudct size:52x52x27mm(LxWxH)	<ul style="list-style-type: none"> <li>● RF DALI master,6 in 1 function,support single color,color temperature,RGB,RGBW,RGB+CCT,or switch light control.</li> <li>● Match with RF 2.4G single zone or multiple zone remote control.</li> <li>● 1 DALI address, support DT6 dimming, DT8-TC color temperature, DT8-RGB, DT8-RGBW or DT7 switch.</li> <li>● Rotary encoder switch selects DALI address,support scene, group, unicast and broadcast mode.</li> <li>● For RGB,RGBW,RGB+CCT light types, multiple jump or fade dynamic effects are supported..</li> </ul>	DALI Constant Voltage LED Controller:DA1,DA4,DA4-M,DA4-L,DA5-L DALI Constant Current LED Controller:DA4-C DALI Constant Voltage LED Driver:LPV-150DA-24 DALI Constant Current LED Driver:DA-12A,CXD-21A DALI CCT Constant Current LED Driver:DA-12A-2,CXD-21A-2 DALI Triac Dimmer:DT,DT-B DALI 0-10V Dimmer:DV,DV1 DALI Switch:DH,DH1 DALI Bus Power:DA-PS-L Remote Control:R11,R12,R13,RT1,RT2,RT4,RT5	/
DA-M(WT)	WiFi&RF-DALI Converter		Power supply:DALI bus/24VDC Input signal:WiFi, RF 2.4GHz Output signal:DALI Control distance:30m(Barrier-free space) Proudct size:52x52x27mm(LxWxH)	<ul style="list-style-type: none"> <li>● WiFi &amp; RF DALI master,6 in 1 function,support single color,color temperature,RGB,RGBW,RGB+CCT, or switch light control.</li> <li>● Tuya APP cloud control,support on/off,color temperature and brightness adjust,delay turn on/off light,timer run,scene edit and music play function.</li> <li>● Voice control, support for Amazon Alexa,Tmall Genie speakers.</li> <li>● Match with RF 2.4G single zone or multiple zone remote control optional.</li> <li>● 1 DALI address,support DT6 dimming,DT8-TC color temperature,DT8-RGB,DT8-RGBW or DT7 switch.</li> <li>● Rotary encoder switch selects DALI address,support group, unicast and broadcast mode.</li> <li>● For RGB,RGBW,RGB+CCT light types, multiple jump or fade dynamic effects are supported.</li> </ul>	DALI Constant Voltage LED Controller:DA1,DA4,DA4-M,DA4-L,DA5-L DALI Constant Current LED Controller:DA4-C DALI Constant Voltage LED Driver:LPV-150DA-24 DALI Constant Current LED Driver:DA-12A,CXD-21A DALI CCT Constant Current LED Driver:DA-12A-2,CXD-21A-2 DALI Triac Dimmer:DT,DT-B DALI 0-10V Dimmer:DV,DV1 DALI Switch:DH,DH1 DALI Bus Power:DA-PS-L Remote Control:R11,R12,R13,RT1,RT2,RT4,RT5	/

DA-M(WZ)	Zigbee&RF-DALI Converter		<p>Power supply: DALI bus/24VDC  Input signal: Zigbee 3.0, HUE APP, RF 2.4GHz  Output signal: DALI  Control distance: 30m (Barrier-free space)  Product size: 52x52x27mm (LxWxH)</p>	<ul style="list-style-type: none"> <li>● Zigbee &amp; RF DALI master, 6 in 1 function, support single color, color temperature, RGB, RGBW, RGB+CCT or switch light control.</li> <li>● Tuya APP cloud control, support on/off, color temperature and brightness adjust, delay turn on/off light, timer run, scene edit and music play function.</li> <li>● Philips HUE APP control by connect with Philips HUE bridge.</li> <li>● Voice control, support for Amazon Alexa, Tmall Genie speakers.</li> <li>● Match with RF 2.4G single zone or multiple zone remote control optional.</li> <li>● 1 DALI address, support DT6 dimming, DT8-TC color temperature, DT8-RGB, DT8-RGBW or DT7 switch.</li> <li>● Rotary encoder switch selects DALI address, support group, unicast and broadcast mode.</li> <li>● For RGB, RGBW, RGB+CCT light types, multiple jump or fade dynamic effects are supported.</li> </ul>	<p>DALI Constant Voltage LED Controller: DA1, DA4, DA4-M, DA4-L, DA5-L  DALI Constant Current LED Controller: DA4-C  DALI Constant Voltage LED Driver: LPV-150DA-24  DALI Constant Current LED Driver: DA-12A, CXD-21A  DALI CCT Constant Current LED Driver: DA-12A-2, CXD-21A-2  DALI Triac Dimmer: DT, DT-B  DALI 0-10V Dimmer: DV, DV1  DALI Switch: DH, DH1  DALI Bus Power: DA-PS-L  Remote Control: R11, R12, R13, RT1, RT2, RT4, RT5</p>	/
DMC	DALI/DMX512 Converter		<p>Input voltage: 12-48VDC  Input signal: DALI (DT6) / DMX512  Output signal: DMX512 / DALI (DT6)  Product size: 48x110x67mm (LxWxH)</p>	<ul style="list-style-type: none"> <li>● Convert DALI (DT6) signal to DMX512 signal to realize DALI control of DMX devices.</li> <li>● Convert DMX512 signal to DALI signal to realize DMX control of DALI devices.</li> <li>● 3 button operation with digital display.</li> <li>● Standard rail mount.</li> </ul>	<p>DT6 Dimming DALI Master  DMX512 Master</p>	/