Constant	Voltage Power R	epeater				
Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
EV1	1 Channel Constant Voltage Power Repeater	Marriage 12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Input/Output voltage:5-36VDC Output current:8A Output power:40-288W Proudct size:97x33x18mm(LxWxH)	 To receive 1 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to single color constant voltage LED strip or module. 	1 Channel Constant Voltage LED Controller:V1,V1-K,V1-C,V1-M,V1-W 1 Channel Constant Voltage LED Panel Controller:T1-K,T1-1	EV1, EV1-S, EV1-X Contrast: Common: All are 1 Channel Constant Voltage Power
EV1-S	1 Channel Constant Voltage Power Repeater	o specific Control	Input/Output voltage:12-24VDC Output current:15A Output power:180-360W Proudct size:175x45x27mm(LxWxH)	 To receive 1 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to single color constant voltage LED strip or module. 	1 Channel Constant Voltage LED Controller:V1,V1-K,V1-C,V1-M,V1-W 1 Channel Constant Voltage LED Panel Controller:T1-K,T1-1	Repeater. Difference: 1. Output current is different: EV1 output 8A EV1-S output 15A EV1-X output 30A 2. Input/output voltages are different: EV1 input/output voltages:5-36VDC EV1-S, EV1-X input/output voltages:12-24VDC 3. Product sizes are different.
EV1-X	1 Channel Constant Voltage Power Repeater		Input/Output voltage:12-24VDC Output current:30A Output power:360-720W Proudct size:107x75x24.5mm(LxWxH)	 To receive 1 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to single color constant voltage LED strip or module. 	1 Channel Constant Voltage LED Controller:V1,V1-K,V1-C,V1-M,V1-W 1 Channel Constant Voltage LED Panel Controller:T1-K,T1-1	
EV2	2 Channel Constant Voltage Power Repeater		Input/Output voltage:12-36VDC Output current:2CH, 8A/CH Output power:2x(96-288)W Proudct size:175x45x27mm(LxWxH)	 ■ To receive 2 channel PWM signal control. ■ Power repeater in series or in parallel to expand output unlimitedly. ■ Apply to single color or color temperature constant voltage LED strip or module. 	2 Channel CCT Constant Voltage LED Controller:V2,V2-L,V2-C,V2-M,V2-W 2 Channel CCT Constant Voltage LED Panel Controller:T2-1,T2-K	/
EV3	3 Channel Constant Voltage Power Repeater	The server was the training of the	Input/Output voltage:12-36VDC Output current:3CH, 6A/CH Output power:3x(72-216)W Proudct size:175x45x27mm(LxWxH)	 To receive 3 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to single color or RGB constant voltage LED strip or module. 	3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 3 Channel RGB Voltage LED Panel Controller:T3,T3-1,T3-K	EV3, EV3-X, EV3-H Contrast: Common: All are 3 Channel Constant Voltage Power
EV3-X	3 Channel Constant Voltage Power Repeater	ar and the	Input/Output voltage:12-36VDC Output current:3CH, 10A/CH Output power:3x(120-360)W Proudct size:107x75x24.5mm(LxWxH)	 To receive 3 channel PWM signal control. ● Power repeater in series or in parallel to expand output unlimitedly. ● Apply to single color or RGB constant voltage LED strip or module. 	3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 3 Channel RGB Voltage LED Panel Controller:T3,T3-1,T3-K	Repeater. Difference: 1. Output current is different: EV3 output 6A/CH EV3-X output 10A/CH EV3-H output 5A/CH 2. Output voltages are different: EV3, EV3-X output voltages:12-36VDC EV3-H output voltages:12-60VDC 3. Product sizes are different.
EV3-Н	3 Channel Constant Voltage Power Repeater (12-60V)		Input/Output voltage:12-60VDC Output current:3CH,5A/CH Output power:3x(60-300)W Proudct size:175x45x27mm(LxWxH)	 ■ To receive PWM signal control. ■ Power repeater in series or in parallel to expand output unlimitedly. ■ Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module. 	3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 3 Channel RGB Voltage LED Panel Controller:T3,T3-1,T3-K	
EV4	4 Channel Constant Voltage Power Repeater		Input/Output voltage:12-36VDC Output current:4CH,5A/CH Output power:4x(60-180)W Proudct size:175x45x27mm(LxWxH)	 To receive 4 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module. 	4 Channel RGBW Voltage LED Controller:VP,V4,V4-L,V4-M,V4-W 4 Channel RGBW Voltage LED Panel Controller:T4,T4-1	EV4, EV4-WPS, EV4-X Contrast: Common:
EV4-WPS	Waterproof 4 Channel Constant Voltage Power Repeater		Input/Output voltage:12-36VDC Output current:4CH, 5A/CH Output power:4x(60-180)W Proudct size:153x57x34mm(LxWxH)	 To receive 4 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module. Waterproof to IP67 for outdoor and wet environments. 	1 Channel Constant Voltage LED Controller:V1,V1-K,V1-C,V1-M,V1-W 2 Channel CCT Constant Voltage LED Controller:V2,V2-L,V2-C,V2-M,V2-W 3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 4 Channel RGBW Voltage LED Controller:VP,V4,V4-L,V4-M,V4-W	All are 4 Channel Constant Voltage Power Repeater. Difference: 1. Output current is different: EV4, EV4-WPS output 5A/CH EV4-X output 8A/CH 2. Input/output voltages are different: EV4, EV4-WPS input/output voltages:12-36VDC EV4-X input/output voltages:12-24VDC 3. Product sizes are different.
EV4-X	4 Channel Constant Voltage Power Repeater	e.com	Input/Output voltage:12-24VDC Output current:4CH,8A/CH Output power:4x(96-192)W Proudct size:107x75x24.5mm(LxWxH)	 ■ To receive 4 channel PWM signal control. ■ Power repeater in series or in parallel to expand output unlimitedly. ■ Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module. 	4 Channel RGBW Voltage LED Controller: VP, V4, V4-L, V4-M, V4-W 4 Channel RGBW Voltage LED Panel Controller: T4, T4-1	
EV4-H	4 Channel Constant Voltage Power Repeater (12-60V)		Input/Output voltage:12-60VDC Output current:4CH, 5A/CH Output power:4x(60-300)W Proudct size:175x45x27mm(LxWxH)	 ◆ To receive 4 channel PWM signal control. ◆ Power repeater in series or in parallel to expand output unlimitedly. ◆ Apply to single color, dual color, RGB or RGBW constant voltage LED strip or module. 	1 Channel Constant Voltage LED Controller:V1,V1-K,V1-C,V1-M,V1-W 2 Channel CCT Constant Voltage LED Controller:V2,V2-L,V2-C,V2-M,V2-W 3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 4 Channel RGBW Voltage LED Controller:VP,V4,V4-L,V4-M,V4-W	/

EV5	5 Channel Constant Voltage Power Repeater	T. Com	Input/Output voltage:12-24VDC Output current:5CH, 5A/CH Output power:5x(60-120)W Proudct size:107x75x24.5mm(LxWxH)	 To receive 5 channel PWM signal control. Power repeater in series or in parallel to expand output unlimitedly. Apply to RGB+CCT constant voltage LED strip or module. 	5 Channel RGB+CCT Constant Voltage LED Controller:V5-M,V5,V5-L	/
EV5-L	5 Channel Constant Voltage Power Repeater (12-48V)	The state of the s	Input/Output voltage:12-48VDC Output current:5CH, 4A/CH Output power:5x(48-192)W Proudct size:179x56x30mm(LxWxH)	 ◆ To receive 5 channel PWM signal control. ◆ Power repeater in series or in parallel to expand output unlimitedly. ◆ Apply to single color, dual color, RGB or RGBW or RGB+CCT constant voltage LED strip or module. 	1 Channel Constant Voltage LED Controller:V1,V1-K,V1-C,V1-M,V1-W 2 Channel CCT Constant Voltage LED Controller:V2,V2-L,V2-C,V2-M,V2-W 3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 4 Channel RGBW Voltage LED Controller:VP,V4,V4-L,V4-M,V4-W 5 Channel RGB+CCT Constant Voltage LED Controller:V5-M,V5,V5-L	/
Constant	Current Power I	LED Repeater				
		D. .	D	V P	D 11D 1	
Model Name	Product Name	Pictrue	Parameters	Key Feature	Recommended Products	Distinguish Between Similar Products
EC4 (150-500mA)	4 Channel Constant Current Power Repeater	Pictrue	Input voltage:24-48VDC Output voltage:3-45VDC Output current:4CH, 150-500mA/CH Output power:4x(0.45-22.5)W Proudct size:175x45x27mm(LxWxH)	• To receive 4 channel PWM signal control. • DC to DC constant current output, 8 levels output current selectable (150-500mA, 50mA intervals). • Power repeater in parallel to expand output unlimitedly. • Apply to single color, dual color, RGB or RGBW constant current LED lamps.	1 Channel Constant Voltage LED Controller:V1,V1-L,V1-K,V1-C,V1-M 2 Channel CCT Constant Voltage LED Controller:V2,V2-L,V2-C,V2-M,V2-W 3 Channel RGB Voltage LED Controller:V3,V3-L,V3-C,V3-M,V3-W 4 Channel RGBW Voltage LED Controller:VP,V4,V4-L,V4-M,V4-W	Distinguish Between Similar Products /